DESIGN NOTESThe following section outlines design issues considered during the layout of the conceptual street plans.

76th Street

- Collector street with 12-foot lanes and parking provided on both sides
- Existing continuous center turn lane assumed to be replaced with additional parking on north side. Parking to serve BNSF uses and commercial areas to north and south 80th Street
- NE 80th becomes a local access street from Redmond Way to NE 164th, a collector with continuous left turn from NE 164th to 166th, and a collector east of 166th.

83rd Street

- NE 83rd becomes a local access (green) street from 158th to NE 164th, and a collector with continuous left turn from NE 164th to 166th.
- Enhanced 20 foot sidewalk on north side provides for improved pedestrian environment landscaping. Connects through park to school.
- Between 158th and 160th assumes street is shifted to north to correct offset intersection. Parking and larger sidewalk is therefore provided on south side.
- Assumes transit service is accommodated elsewhere.
- Curb radii generally 25 feet at (similar to Town Center) with bulbouts except between 164th and 166th.

• No turn pockets provide except between 164th and 166th (Collectors)

85th Street

- Collector street with 10-foot lanes (as agreed to with the City) and a continuous 12-foot left-turn
- Redmond City Council has expressed concern over a move from four to three lanes. Three lanes are shown here to illustrate the concept. Any changes to the existing street lane configuration will require City Council approval.
- 8-foot parking lanes provided on both sides
- 4-foot bicycle lanes (as agreed to with the City) provided on both sides
- EB right-turn lane at 164th Street provided
- Curb radii generally 25 feet (similar to Town Center)
- Bulb outs at most intersections
- Bus zone curb stop on WB 85th on west side of 160th Ave
- Articulated bus turns accommodated from NB 161st Ave to WB 85th St

158th Ave NE	• Curb radii 25 feet at 83 rd (similar to Town Center)
Local street with pedestrian emphasis	• Bulbouts assumed at NE 83 rd
• No turn lanes at 83 rd	Existing curb maintained where possible
Curb radii generally 25 feet (similar to Town Center)	 Bike lanes are not provided on Cleveland Street (bike share travel lane) hence bike lanes on Redmond Way terminate just north of Redmond Way allowing bike traffic to merge rather than bringing the lanes to the intersection.
Bulb outs at intersections	
	161st Ave NE
• 10-foot travel lanes	
	Local street with 10-foot travel lanes.
Parking both sides	
	Wide lanes provide in vicinity of Redmond Way
160 th Ave NE	
	Green Street: enhanced sidewalk and landscaping on one side
 Collector street with 11 foot travel lanes and 5-foot bike lanes 	
 Left turns provided to other collector streets (85th and Redmond Way). No left turn at 83rd (local street). 	 Left turns provided to other collector streets (85th and Redmond Way). No left turn at 83rd (local street).
	 Parking restricted in vicinity of 85th to allow for turn lane
Parking restricted in vicinity of 85th to allow for turn lane	
	Parking on both sides
Parking on one side	
	• Curb radii 25 feet at 83 rd (similar to Town Center)

urn lanes provided
outs at intersections with 25-foot radius (as per Town Center)
ntial extension to NE 79^{th} . City owned property may be used for access (intersection may be t)
ector street with 12-foot lanes and continuous left turn to Redmond. Continuous left turn is sped from Redmond Way to Bear Creek Parkway.
outs provided at Redmond Way and Cleveland Street
mond City Council has expressed concern over a move from four to three lanes. Three lanes hown here to illustrate the concept. Reduced number of lanes allows for wider curb lanes to as a bike route and allows for wider sidewalks. Sidewalks a priority due to designation as estrian connector and proximity to school. Any changes to the existing street lane guration will require City Council approval.
turn provided from 166 th northbound to Redmond Way (collector). Left turn also provided to eland, as this is a major access point between Town Center and Cleveland Street. Otherwise, priority in Old Town is to minimize crossing distances for pedestrians and maximize estrian/landscaped areas; hence no additional turn pockets are provided.
priority in Old Town is to minimize crossing distances for pedestrians and maximize
r 3

168h Ave NE

- Collector street with 12-foot lanes and parking both sides.
- Minor collector accessing the school

Avondale Road

- Avondale Road is shown for the purpose of determining an approximate alignment with Bear Creek Parkway. It was outside the immediate focus of work for Phase I of the TMP and further work is required to determine a configuration for Avondale Road. Issues to resolve include bike lanes vs. wide curb lanes, presence of HOV lanes, number of lanes turn lanes, etc...
- For the purpose of demonstrating a potential alignment, a radius of 346 feet was chosen for Avondale Road in the vicinity of NE 79th. Design parameters would be further explored during the design process. If a tighter radius or narrower cross-section is found to be desirable, right of way needs may be reduced
- Preferred design concept for Avondale at 79th is a redesigned intersection with Avondale Road as a through movement to 170th Avenue. Maintaining the existing intersection may also be considered with left turns to 170th Avenue. The right of way for NE 170th is narrow (approx. 50 feet), and will require substantial additional right of way under both options if the City is to pursue the full cross-section envisioned (including planned HOV lanes).
- HOV lanes are shown in both directions as per the City's existing long-term plan. A transit concept
 was not developed under phase I of the Redmond Transportation Master Plan (TMP). Major
 changes to circulation in the downtown in phase I of this plan suggests the need to revisit how
 transit will function in the downtown, the role of HOV lanes entering the downtown and how
 HOV facilities will transition to other facilities such as merge to general use lanes or possibly a
 form of transit facility on the BNSF.

- For the purposes of this conceptual layout it is assumed that HOV lanes entering on Avondale Road would end at NE 79th Street becoming a general purpose lane. Eastbound HOV lanes on Avondale Road and Redmond Way would begin, respectively at Redmond Way and east of Bear Creek Parkway intersection. The HOV lane entering on Redmond Way would end at the intersection at Break Creek Parkway. Signal priority would allow HOV traffic to merge to the general-purpose lanes.
- Local access to 170th Place, currently provided at Avondale Road and NE 79th, is assumed to be
 accommodated elsewhere. Providing access to 170th Place from Avondale Road provides for an
 awkward intersection that could raise operational and safety concerns and was therefore
 considered incompatible with the design concept of creating an improved arterial street along Bear
 Creek Parkway and Avondale Road.
- Outside travel, HOV lane and turn lanes will be 12' wide.

Bear Creek Parkway

- Lane expansion through Town Center area should be toward southern ROW where possible. Lane expansion south of Town Center generally remains within the existing ROW.
- Curb radii will be as existing to all Town center entrances.
- No signals provided at 164th, 168th, and NE 74th. Emphasis in placed on accommodating through traffic.
- No sidewalk provided on south side in vicinity of Town Center. Assumes trail provided in park area.
- Pedestrian crossing to park south of Bear Creek Parkway may occur at 166th or mid-block west of 166th to align with Town Center design concept.

Cleveland Street • Right turn pockets along Bear Creek Parkway in the vicinity of Town Center were not included to reduce the footprint of the roadway. Curb bulbouts applied to all corners. • No pedestrian crossing assumed at NE 74th. Crossing provided at NE 76th. This may be reconsidered due to commercial uses opposite Town Center in the vicinity of NE 74th. • 10-foot lanes assumes no buses on Cleveland. • New alignment (74th to Redmond Way) should avoid pump station at 74th. • East end of Cleveland (to Redmond Ave) realigned to better manage traffic with existing signal. • Pedestrian signals indicated (as placeholders) for free rights from Redmond Way to Bear Creek • Sidewalks will be as shown in sections or as existing where applicable. Parkway and from Bear Creek Parkway to Redmond Way. Needs further consideration during design. • New alignment (74th to Redmond Way) should avoid natural area (Heron rookery). **Leary Way** • Outside travel lane and turn lanes will be 12' wide. • 5' Bike lanes will be added from the bridge to BNSF ROW where possible. Bike lanes taper at bridge to conform to existing width. Eastbound, from bridge, assumes 12 foot multi-use path adjacent to roadway connecting to crosswalk at Bear Creek Parkway. (bicycle traffic to cross at crosswalk separate from high volume double right turn to Bear Creek). Transition from multi-use Bicycle traffic will be accommodated in 12' curb lane. As per bike network concept, assumes BNSF path (may continue as off-street path to BNSF) to on-street bike lane must be resolved during provides major route for local and through bicycle traffic design process Connection to Redmond Way Eastbound (170th Ave) will merge with current DEA plans, and • Bike lanes transition to BNSF ROW (not shown). Assumes majority of bicycle traffic will use BNSF single HOV lane each direction. to connect to rest of bicycle network. • Realignment to the west of existing ROW at Redmond Way will be accepted to facilitate the • Sidewalks will be as shown in sections or as existing where applicable. Avondale realignment. Assumes pedestrian/design connection between Cleveland and BNSF • Leary remains as existing between Cleveland Street NE 80th

Redmond Way Parking on south side of street. Median assumed to be landscaped unless indicated as continuous left turn. Outside travel lane and turn lanes will be 12' wide. Sidewalks will be as shown in sections or as existing where applicable. Where possible, existing curbs are maintained. Curb radii to the north of Redmond Way generally larger than on the south side. General intent on south side is to slow vehicle traffic as it enters the pedestrian zone of the Old Town area. Redmond Way, 160th to 161th, shows wider turn lanes (12') to take advantage of wider right of way Conceptual design assumes some level of access management is undertaken during design. Onstreet parking locations are shown conceptually. Driveway access is generally shown as a gap in parking. In some cases (where no gap in parking is shown) it is assumed that access is provided from side streets. Westbound, right turn lane to 164th is desirable. Requires right of way. Under concept, NE 79th no longer connects to Redmond Way. Potential to swap right of way required for turn lane for portion of right of way on NE79th. Lane configuration in vicinity of 170th differs from access management design work currently being done (DEA). Drawings are intended to represent long-term plan and therefore include HOV lanes currently in the City's plan and assume major change in circulation.

BEAR CREEK PARKWAY OPTIONS The following drawings include three potential alignment options for extending Bear Creek Parkway from 164th NE, through Leary Way, to Redmond Way. Option B is illustrated in the details drawings (previous section).